



ANTIALLERGENIC ESD WRIST STRAP



Wrist band: Conductive (silver) fibres with polyester, very flexible, washable without conductivity loss, Lengthening: 25 % (ASTM D882 test mode), blue

Coiled cord: Length: 3 m, Resistance: 1 MOhm (in the snap fastener), blue



| Order Code | Coil cord connections |
|------------|------------------------------------|
| DLB-100 | 10 mm female SF / 4 mm banana plug |
| DLB-101 | 10 mm female SF / 10 mm female SF |

(SF = snap fastener)

DUAL ESD WRIST STRAP



Wrist band: Elastic Nylon with silver plated threads, very flexible, washable without conductivity loss, Lengthening: 25 % (ASTM D882 test mode), blue

Coiled cord: 7-Strand Twin tinsel wire, length: 3 m, Resistance: 1 MOhm (in the snap fastener), black



| Order Code | Coil cord connections |
|------------|---|
| DLB-103 | 10 mm dual female SF / 90° mono jack plug |

(SF = snap fastener)

ESD HEEL GROUNDER



Resistor: 1 MOhm, Black / White, Ribbon: 55 cm long nylon/ polyester grounding band with 8 conductive strands, rubber grounder: 38 mm width, three layer laminated, rubber sole. Outer conductive black rubber layer < 10⁵ Ohm





| Order Code | |
|------------|----------------------|
| DLB-049 | with velcro fastener |
| DLB-050 | with quick clasp |

ESD SOLE GROUNDER



Resistor: 1 MOhm, Black / White, Ribbon: 30 cm long nylon/ polyester grounding band with 8 conductive strands, Velcro: 20 mm width, Black, Rubber grounder: three layer laminated, rubber sole. Outer conductive black rubber layer $< 10^5 \, \text{Ohm}$



| Order Code | Size |
|------------|---------|
| DLB-073/** | XS - XL |

EARTH BONDING POINTS

AIJGO-7.2/A

AIJGO-7.2/B





| Order Code | | | Connections |
|------------|--|---------|----------------|
| AIJGO-7 | | 2 x | 10 mm male SF |
| AIJGO-7.1 | | 2 x 4 m | nm banana plug |

2 x 4 mm banana plug, 1 x 10 mm male SF 1 x 4 mm banana plug, 2 x 10 mm male SF

(SF = snap fastener)

EARTH BONDING POINTS - ALUMINIUM





| Order Code | Connections |
|------------|---|
| AIJGO-7.3 | 2 x 4 mm banana plug |
| AIJGO-7.4 | 2 x 10 mm male SF |
| AIJGO-7.5 | 2 x 4 mm banana plug, 2 x 10 mm male SF |

(SF = snap fastener)

